

# Bảng thông số sản phẩm

Thông số kỹ thuật



APC Smart-UPS On-Line, 2200VA,  
Tower, 230V, 8x C13+2x C19  
IEC outlets, SmartSlot, Extended  
runtime, W/O rail kit

SRT2200XLI

## Overview

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Presentation | High density, double-conversion on-line power protection with scalable runtime. |
| Lead time    | Usually in Stock                                                                |

## Main

|                        |                                                                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main Input Voltage     | 230 V                                                                                                                                                        |
| Other Input Voltage    | 220 V<br>240 V                                                                                                                                               |
| Main Output Voltage    | 230 V                                                                                                                                                        |
| Other Output Voltage   | 220 V<br>240 V                                                                                                                                               |
| Rated power in W       | 1980 W                                                                                                                                                       |
| Rated power in VA      | 2200 VA                                                                                                                                                      |
| Plug standard          | BS1363A British<br>IEC 60320 C20<br>Schuko CEE 7 / EU1-16P                                                                                                   |
| Output connection type | 8 IEC 60320 C13<br>2 IEC Jumpers<br>2 IEC 60320 C19                                                                                                          |
| Cable length           | 2.44 m                                                                                                                                                       |
| Number of cables       | 1                                                                                                                                                            |
| Battery type           | Lead-acid battery                                                                                                                                            |
| Provided equipment     | CD with software<br>Country-specific detachable power cord<br>Documentation CD<br>Installation guide<br>Removable support feet<br>USB cable<br>Warranty card |

## General

|                                     |              |
|-------------------------------------|--------------|
| Product web sub-family              | High density |
| Number of power module              | 1400         |
| Number of power module free slots   | 0            |
| Number of power module filled slots | 0            |
| Redundant                           | No           |

Physical

|                     |                       |
|---------------------|-----------------------|
| Colour              | Black                 |
| Height              | 43.2 cm               |
| Width               | 8.5 cm                |
| Depth               | 58.4 cm               |
| Net weight          | 25 kg                 |
| Mounting location   | Front                 |
| Mounting preference | Lower                 |
| Mounting mode       | Rack-mounted with kit |
| Two post mountable  | 0                     |
| USB compatible      | Yes                   |
| Mounting position   | Vertical              |

Input

|                      |                                    |
|----------------------|------------------------------------|
| Network frequency    | 40...70 Hz auto-sensing            |
| Input voltage limits | 100...275 V adjustable (half load) |

Output

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Maximum configurable power in W  | 1980 W                                 |
| Harmonic distortion              | Less than 2 %                          |
| Output frequency                 | 50/60 Hz +/- 3 Hz sync to mains        |
| Crest factor                     | 3 : 1                                  |
| UPS type                         | Double conversion online               |
| Wave type                        | Sine wave                              |
| Bypass type                      | Internal bypass (automatic and manual) |
| Maximum configurable power in VA | 2200 VA                                |

Conformance

|                        |                                                                                    |
|------------------------|------------------------------------------------------------------------------------|
| Product certifications | CE<br>EAC<br>RCM<br>VDE                                                            |
| Marking                | CE Mark                                                                            |
| Standards              | EN/IEC 62040-1:2019/A11:2021<br>EN/IEC 62040-2:2006/AC:2006<br>EN/IEC 62040-2:2018 |

Environmental

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C               |
| Relative humidity                     | 0...95 % non-condensing |
| Operating altitude                    | 0...10000 ft            |
| Ambient air temperature for storage   | -15...45 °C             |
| Storage Relative Humidity             | 0...95 % Non-condensing |
| Storage altitude                      | 0.00...15240.00 m       |

|                         |           |
|-------------------------|-----------|
| Acoustic level          | 55 dBA    |
| Heat dissipation        | 703 Btu/h |
| IP degree of protection | IP20      |

### Batteries & Runtime

|                                        |                                                                                                                                                                               |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of battery filled slots         | 1                                                                                                                                                                             |
| Number of battery free slots           | 0                                                                                                                                                                             |
| Battery recharge time                  | 3 h                                                                                                                                                                           |
| Number of battery replacement quantity | 1                                                                                                                                                                             |
| Additional information                 | Configurable for 220 : 230 or 240 nominal output voltage                                                                                                                      |
| Battery voltage                        | 72 V                                                                                                                                                                          |
| Battery charger power                  | 122 W rated                                                                                                                                                                   |
| Battery power in VAH                   | 367 VAh runtime                                                                                                                                                               |
| Battery life                           | 3...5 year(s)                                                                                                                                                                 |
| Replacement battery                    | <a href="#">APCRBC141</a>                                                                    |
| Battery option                         | SRT72BP 1 1101 VAh<br>SRT72BP 2 1835 VAh<br>SRT72BP 3 2569 VAh<br>SRT72BP 4 3303 VAh<br>SRT72BP 5 4037 VAh<br>SRT72BP 6 4771 VAh<br>SRT72BP 8 6239 VAh<br>SRT72BP 10 7707 VAh |
| Extended runtime                       | 1                                                                                                                                                                             |

### Communications & Management

|                     |                                                    |
|---------------------|----------------------------------------------------|
| Free slots          | 1                                                  |
| Control panel       | Multifunction LCD status and control console       |
| Alarm               | Audible and visible alarms prioritized by severity |
| Emergency power off | Yes                                                |

### Surge Protection and Filtering

|                   |       |
|-------------------|-------|
| Surge energy rate | 340 J |
|-------------------|-------|

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 24.6 cm  |
| Package 1 Width              | 81 cm    |
| Package 1 Length             | 59.9 cm  |
| Package 1 Weight             | 30.84 kg |

### Offer Sustainability

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| Sustainable offer status | Green Premium product                            |
| REACH Regulation         | <a href="#">REACH Declaration</a>                |
| EU RoHS Directive        | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free             | Yes                                              |

|                             |                                                                                                                             |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| RoHS exemption information  | Yes                                                                                                                         |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile         | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product                                                                                                    |
| Take-back                   | Take-back program available                                                                                                 |

### Contractual warranty

|          |                                                                       |
|----------|-----------------------------------------------------------------------|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|-----------------------------------------------------------------------|

Thay thế được đề xuất