



## General

Provided equipment	CD with software Documentation CD USB cable
--------------------	---

## Physical

Number of rack unit	0U
Colour	Black
Depth	44 cm
Height	21.6 cm
Net weight	27.5 kg
Width	17 cm

## Input

Network frequency	47...63 Hz
Plug standard	IEC 320 C20
Input voltage limits	170...300 V adjustable 180...287 V
Inputvolt_other	220 V 240 V
Input voltage	230 V

## Output

Rated power in W	1300 W
Maximum configurable power in W	1300 W
Harmonic distortion	Less than 5 % at full load
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave

Nb of power socket outlets	6 IEC 320 C13 1 IEC 320 C19
Output voltage	230 V

## Conformance

Product certifications	C-Tick CE EAC GOST SABS VDE
Equipment protection policy	3 years : \$250

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Heat dissipation	135 Btu/h

## Battery

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0

## Communication

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------