



## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks

## General

Provided equipment	CD with software Documentation CD Installation guide Rack mounting brackets USB cable
Product web sub-family	Entry level
Performance multiplier	1
Number of tare power	26 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

## Physical

Number of rack unit	2U
Colour	Black
Depth	47 cm
Height	8.9 cm
Mounting location	Front
Mounting preference	Lower

Net weight	26.2 kg
Mounting mode	Rack-mounted
Two post mountable	1
USB compatible	Yes
Width	48 cm

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C20
Input voltage limits	180...287 V
Number of cables	1
Input voltage	230 V

## Output

Rated power in W	1300 W
Maximum configurable power in W	1300 W
Harmonic distortion	Less than 5 %
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 IEC 320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	2000 VA
Rated power in VA	2000 VA
Transfer time	8 ms typical : 10 ms maximum

## Conformance

Product certifications	C-Tick CE EAC GOST IRAM SABS VDE
Marking	GS Mark
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft

Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	42 dBA
Heat dissipation	81 Btu/h
Show note OP temperature	No

### Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	A
Battery charger power	144 W rated
Battery power in VAH	432 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

### Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

### Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

### Packing Units

Package 1 Weight	30.16 kg
Package 1 Height	25 cm
Package 1 width	59 cm
Package 1 Length	60 cm
Number of Units in Package 3	16

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

---